




## WiFi-USB gateway

This device is compatible with any controllers developed with Dinacell NG technology.



## **GD-WIFI** Gateway device

The link of this device to the Dinacell unit controller will allows to configure, calibrate and obtain information on the installation status through the Tools ng2 application.



Parameter		Units	Specifications
Model		-	GD-WiFi
Power supply		VDC	5
Temp range.	Operating	°C (°F)	0 <b>+70</b> (+32+158)
	Storage		-10 +70 (-14 +158)
WiFi	Wifi Frequency	GHz	2.4
	Output power	dBm	18
	Input sensivity	dB	-85
USB Connectivity	Interface	-	USB Type A + OTG to mini USB adapter
	Version	-	2.0
Casing material		-	Fireproof plastic ABS
Protection class		-	IP50

For more information

Document Ref.: D1733-01

Publication date: 21/03/2022

## www.elevatormotors.com

ELEVATOR MOTOR CORPORATION. (EMCO) 80 Carolyn Boulevard, NY- 11735 Farmingdale, USA Phone. (+1) 6312934440 Fax. (+1) 6312932714



## OFFICIAL USA DISTRIBUTOR OF DINACELL ELECTRÓNICA S.L.

Dinacell Electrónica S.L. reserves the right to add, modify and/or delete content of the document without prior notice. The content indicated here should be used as general product information. It should not be interpreted as a guarantee of quality or durability.